

KITO CX SERIES CHAIN BLOCKS



Applications

- ✔ Used in mining, construction, engineering, power transmission fabrication, manufacturing, processing
- ✔ Ideal for the assembly line, work station, job site, workshop

Features

- ✔ Available in 0.25T and 0.5T.
- ✔ Standard lift height of 2.5 metres.
- ✔ Optional lift heights also available upon request.
- ✔ Compact and lightweight.
- ✔ Wide internal diameter of hooks (top and bottom).
- ✔ Low headroom on each model.
- ✔ Smart body with non-protuding bolt.
- ✔ Equipped with overload limiter.
- ✔ High strength load chain.
- ✔ Hook latch with tip supporting structure.

Compact design with an integral aluminium body, extremely lightweight of 2.4kg. Both models of the KITO CX Series are equipped with an overload limiter as standard.

Capacity: 250 – 500kg

KITO CX Series Chain Blocks

Specifications

Capacity	Part No.	Headroom (mm)	Load Chain Dia (mm) x fall	Weight (kg)	Load Chain Dia x Pitch (mm)	Load Chain Part No.	Heights of Lift (m)
250kg	45377	217	3.2 x 1	2.4	3.2 x 9	44835	2.5
500kg	40322	260	4.3 x 1	4.5	4.3 x 12	40328	2.5

*Optional lift heights available.

Compact and extremely powerful

Compact design without protruding bolts

Equipped with overload limiter

Nickel-plated load chain

Grade T, series V (G100)
in accordance with standard
EN818-7, Strength 1,000 N/mm

Corrosion-resistant hand chain

Guided hook latch

Top and load hook

Hook with large internal diameter

Top and load hook



KITOPWB

Premium Quality Products

For more information:

Call 1300 792 262

Visit www.kitopwb.com.au

