

FLEXIBLE ALD MOUNTING SUPPORT

FLEXIBLE ALD MOUNTING SUPPORT

is designed for installation of 1-3 antenna line device units such as TMA, filters etc. By adding expansion for ALD mounting support it is possible to install up to 6 units of antenna line device.

FLEXIBILITY

The flexible ALD mounting support can handle a wide range of all common frame leg designs, round, square, angle etc. Thanks to the unique design. You can choose the position of the included mounting tube. This can be done by turning the tube holder in reverse position or mount the tube

holder on the inside or the outside of the clamp. These options makes the support very flexible and easy to optimize for your type of installation.

QUALITY

All components are made of anodized aluminium and acid proof stainless steel which gives the support excellent corrosion resistance.

EASY ASSEMBLEY

The choice of materials and design makes the product very light which makes the handling and installation very easy.









ORDER AND TECHNICAL INFORMATION					
DRAWING NO:	CD 990664 / CD 990665				
FUNCTION DESCRIPTION:	Flexible ALD mounting support in one level for installation of 1-3 antenna line device units. For Installation directly on tower leg or other vertical structures of various size and shape. 3 pc of mounting tubes are included. Expansion for ALD mounting support to be added on the flexible ALD mounting support. Containing 1pc tube holder and 1pc mounting tube.				
MOUNTING SPAN:	TUBES:	SQUARE PROFILES:	90° AN	GLE:	60° ANGLE: ✓
Minimum Maximum Mounting tubes	Ø25 mm (1,0 in) Ø120 mm (4,7 in) Ø60 x 3 L=400 mm	35 x 35 mm (1,4 x 90 x 90 mm (3,5 x 3 (2,4 x 3 L=15,7 in)	, ,	5 mm (1,4 x 1,4 in) 0 mm (3,5 x 3,5 in)	40 mm (1,6 in) opening 100 mm 4,0 in) opening
PACKAGE DIMENSIONS:		LENGTH: 405 mm (15,9 in) 550 mm (21,6 in)	WIDTH: 136 mm (5,3 in) 95 mm (3,7 in)	HEIGHT: 136 mm (5,3 in) 95 mm (3,7 in)	WEIGHT: 4,8 kg (10,6 lb) 1,5 kg (3,2 lb)