

Data sheet

LIFELINE HORIZONTAL



GENERAL

Art. no.:	L-0329	E-class number:	40-02-01-90
EAN:	4030281086406	Customs no.:	63079010
Standard:	CEN/TS 16415:2017 EN 795-B:2012		

Data sheet

LIFELINE HORIZONTAL

Temporary horizontal fall protection systems are very popular for assembly work in steel construction, in scaffolding and in general construction.

LIFELINE HORIZONTAL is a portable, very quick to assemble and flexible fastening device. Two people can be secured over a distance of 20 metres as they work.

The system's two carabiners can be attached using slings (for example) to suitable structures such as steel beams, scaffolding or concrete pillars. According to new regulatory certification requirements, the structure used must be configured for a load of 6 kN, since in the event of a fall, the force exerted on the system is limited to a maximum of 6 kN by means of damping elements.

- 20 metre horizontal range
- The structure used only needs to be able to withstand a load of 6 kN
- Flexible horizontal fall protection system for nearly every kind of construction site

FEATURES

Max. service life: 10 Years

Max. number of persons: 2

Area of application:

Construction / Roofer / Carpenter, Metal Construction

DIMENSIONS

Weight: 2,87 kg

MATERIAL

Material: Polyester, Steel
