

Data sheet

SKYSAFE PRO FLEX



GENERAL

Art. no.: L-AUS-0569-1,8

E-class number: 40-02-01-04

EAN: 4030281201236

Customs no.: 56090000

Data sheet

SKYSAFE PRO FLEX

ONE4ALL - The SKYSAFE PRO

Revolutionary, new energy absorber with the large weight range from 50 - 140kg (110 - 310 lbs.) that always withstands a maximum impact of less than 6 kN at a maximum absorber length of 1.75m (5.7 Feet).

The final impact resistance of 22 kN, also in the absorber, before AND after a fall is exceptional as well. SKYSAFE PRO furthermore meets the most relevant international standards in one SINGLE product.

UNIQUE: The built-in, adjustable RESCUE LOOPS! As a result, rescuers need not set up a rescue system and hereby save precious time in a rescue!

Available in four versions with different carabiner combinations:
I-web, Y-web, I-web tie-back, Y-web tie-back.

GENERAL

Internat. standard: AS/NZS 1891.1:2007

FEATURES

Fall indicator

Breaking load, major axis:

50,00 kN

Hand-washing: 40 °C

Suitable for edges: yes

Max. service life: 10 Years

Max. number of persons: 1

Rated load: 140 KG

Rescue Loop: yes

Temperature: from 45 °C to -35 °C

Suspension element: BAND

DIMENSIONS

Size:	1,8m
Weight:	1,65 kg

HARDWARE

Carabiner on anchoring point side:
FS 90 ST ANSI

Carabiner on belt side: KOBRA TRI

MATERIAL

Material:	Polyester, Steel
Webbing material:	Polyester