

Data sheet

SKYSAFE PRO FLEX



GENERAL

Art. no.:	L-AUS-0590-1,8	E-class number:	40-02-01-04
EAN:	4030281186922	Customs no.:	56090000



Data sheet

SKYSAFE PRO FLEX

ONE4ALL - The SKYSAFE PRO

Revolutionary, new energy absorber with the large weight range from 50 - 140kg (110 - 310 lbs.) that always withstands a maximum impact of less than 6 kN at a maximum absorber length of 1.75m (5.7 Feet).

The final impact resistance of 22 kN, also in the absorber, before AND after a fall is exceptional as well. SKYSAFE PRO furthermore meets the most relevant international standards in one SINGLE product.

UNIQUE: The built-in, adjustable RESCUE LOOPS! As a result, rescuers need not set up a rescue system and hereby save precious time in a rescue!

Available in four versions with different carabiner combinations:

I-web, Y-web, I-web tie-back, Y-web tie-back.

GENERAL

Internat. standard: AS/NZS 1891.1:2007

FEATURES

Fall indicator

I all illulcator			
Breaking load, major axis:			
23,00 kN			
Hand-washing:	40 °C		
Suitable for edges:	yes		
Max. service life:	10 Years		
Max. number of persons: 1			
Rated load:	140 KG		
Rescue Loop:	yes		
Temperature:	from 45 °C to -35 °C		
Suspension element:	BAND		



DIMENSIONS

 Size:
 1,8m

 Weight:
 1,28 kg

HARDWARE

Carabiner on anchoring point side:

SNAP HOOK 23kN

Carabiner on belt side: SNAP HOOK 23kN

MATERIAL

Material: Polyester, Steel

Webbing material: Polyester