




Response® Static Safety Lines

Fully certified static safety lines with kernmantle nylon core



FEATURES

- Responsive and reliable
- Low stretch, high strength
- Quick access and excellent knot holding
- Highly visible in Fluro Orange colour
- Certified to AS4142.3, ANSI Z-133 & EN1891 standards
- Manufactured under ISO 9001:2008
- Includes internal year of manufacture and standards marker yarns

RANGE/TECHNICAL

- 11mm 13mm in 200m reels
- 16mm in 100m reels
- Response® LSK constructed with plaited Nylon strands with a Polyester protective jacket
- Response® XT is heat-set, constructed with parallel twisted Nylon strands, with Nylon protective jacket

APPLICATIONS

- Abseiling
- Belay
- Static descent
- Safety and Rescue line
- Access line

Product Code	Size (mm)	Colour	Reel Weight	Reel Length	BreakForce (kg)
Response® L	.sĸ				
PRP1137*	11	White with Blue/Yellow Flecks	18.5 kg	200 m	3475 kg
PRP1107	11	Fluro Orange with Blue/Yellow Flecks	18.5 kg	200 m	3475 kg
PRP1108	11	Black	18.5 kg	200 m	3475 kg
PRP1109*	11	Blue	18.5 kg	200 m	3475 kg
PRP1149*	11	Black with 4 Green Flecks	18.5 kg	200 m	3475 kg
PRP1101R*	11	Green with 4 Black Flecks	18.5 kg	200 m	3475 kg
PRP1114#	11	Rescue1 Fluro Orange with Black Flecks	18.5 kg	200 m	3475 kg
PRP1300	13	Fluro Orange with Black/Yellow Flecks	24.5 kg	200 m	4750 kg
PRP1602*	16	Fluro Orange with Blue/Yellow Flecks	19.5 kg	100 m	6900 kg
Response® X	(T				
PRP1141	11	Tiger Orange with 4 Black Flecks	18.5 kg	200 m	3475 kg
PRP1140*	11	Blue	18.5 kg	200 m	3475 kg
PRP1142#	11	Other colours - *made to order	18.5 kg	200 m	3475 kg

^{*} Made to order in New Zealand but stocked in Australia.

[#] Made to order in both countries. Minimum order quantities and lead time applies.