

Data sheet

## SPEED ATTACH



### GENERAL

Art. no.:	TAC-0004-EU
EAN:	4030281222644
Standard:	EN 353-1:2014

E-class number:	40-02-01-90
Customs no.:	73269098

## Data sheet

# SPEED ATTACH

The new SPEED ATTACH is a runner of the latest generation that can be attached and detached at any point of a C-profile, but comprises two redundant retention systems as usual. Construction and double locking mechanism also prevent reversed placement or opening under load. A green indicator shows secure locking at any time. Therefore, operating errors are virtually impossible. The runner is suitable for back-pull and drag operation. Solid aluminium housing, stainless steel axles and metal guide rollers ensure low wear. Even after a fall, the runner can still be reconditioned.

### FEATURES

Fall indicator

---

Max. number of persons: 1

---

Rated load: 150 KG

---

Patent

---

Temperature: from 45 °C to -30 °C

---

Area of application:

Confined Spaces, High Rack, Permanent Fall Arrest Systems, Power Supplies / -Transmission / Telecommunications, Wind Energy / Offshore Industry

---

### DIMENSIONS

---

Weight: 1,27 kg

---

### HARDWARE

---

Carabiner on device: SWIVEL SHORT

---

Carabiner on rope: SWIVEL SHORT

---

### MATERIAL

Material:

Aluminium, Stainless Steel, Steel

---